



Economical operation, high off-road capability, multi-functionality

The vehicles designed for special military or civil use – e.g. peace-keeping missions, emergency actions – are to meet such requirements as good off-road capability, transportability by air and by rail, effective protection of the crew and the availability of a wide range of types.

RÁBA Jármű Kft. (RÁBA Vehicle Co.) has aimed at the complete fulfilment of these requirements when developing the special truck family. It has resulted in:

- maximal mobility with competitive price/performance ratio,
- 3 payload categories based on family principle,
- maximal uniformity of the components and parts,
- unified cabs meeting the highest ergonomic and comfort requirements,
- wide range of platforms for different purposes,
- optional armoured protection of the crew,
- optional installation of central tyre inflation system,
- optional installation of winches enabling the recovery of the truck itself and that of trucks belonging to the same GVW category,
- transportability by air, in Hercules C130, as well as by rail without restrictions,
- optimal logistic background,
- full-ranging spare parts and maintenance services based on the vehicle family principle,
- a truck family compliant with NATO interoperability.



Types:	H14.206 AE(L)	H18.206 DAE(L)	H25.206 DAE
Engine:			
Power [kW]	206	206	206
Torque (Nm)	1100	1100	1100
Transmission	Fully synchronized mechanic, 9-speed		
Transfer box	2-speed		
Tyres	14.00 R20		
Wheel pattern	4x4	6x6	
Rolling chassis with cab [kg±3%]	8650	10650	10800
Superstructure + payload on road [kg] (for rolling chassis)	7850	9850	13000
Superstructure + payload off road [kg] (for rolling chassis)	6450	8000	13000
Technically allowed GVW [kg]	17500	23500	27800
Technically allowed front axle load [kg]	7500	7500	7800
Technically allowed rear axle load [kg]	10000	2x8000	2x10000
Towing capacity, on road [kg]	15500	14400	11100
Towing capacity, off road [kg]	8000	8000	8000
Climbing ability [°]	30		
Side slope [°]	20		
Fording ability [mm]	1200		

